

### AdVantEdge DWS-4510-01

The DWS-4510-01 is a single stage water treatment approach with an integrated system design, ideal for under-counter household use. The system includes a selected 4.5 x 10 inch arsenic removal cartridge, housing components, i.e., sumps, caps, mounting bracket, faucet (lead-free), shut-off device, and tubing for a complete unit. AdEdge Technologies supplies both the system components and replacement cartridges. The system is available to qualified water treatment distributors and dealers for subsequent re-sale to end users. Replacement cartridges are available through AdVantEdge authorized distributors.



### Specifications

Arsenic Cartridge  
 Materials Housing  
 Mounting  
 Faucet  
 Shut Off Device  
 Arsenic media  
 Water source  
 NSF testing  
 Box/Packaging  
 Dimensions

### Model: DWS-4510-01

4.5 x 10-inch; AdVantEdge Model AD4510S  
 Injection molded polypropylene  
 Painted metal mounting bracket  
 Lead-free faucet with ¼ inch tubing  
 Mechanical countdown shut-off device mounted on bracket  
 AdEdge custom AD33L product  
 Potable water of known microbiological quality (microbiologically safe)  
 Components tested in accordance with NSF protocols, no specific listings  
 Plain white box, with or without label  
 7.5" width / 21" height

### Performance

Rated Cartridge Life            3000 gallons  
 Arsenic concentration        Up to 50 ppb influent arsenic; if higher than 50 ppb please consult AdVantEdge  
 Replacement                    Every 12 months or 3000 gallons, whichever comes first (for 50 ppb arsenic)  
 Rated flow rate                 0.5 gpm  
 Parameters                        AD4510S: arsenic

Contact your local dealer: